



THERMOSTOP INC., 3775 Losch, Longueuil, Québec, Canada, J3Y 5T7, Tél. : (450) 678-8666, Fax. : (450) 678-7765

STANDARD SPECIFICATIONS
GLACE-GUARD™ SLIDER
Section 08 34 13: Cold Storage Doors

PART 1 – GENERAL

1.1 Works by others :

- Metal fabrication, section 05500
- Electrical power supply, division 16
- Structural work, division 5

1.2 Construction requirements :

- Design doors to withstand wind load of 21 psf (velocity of 90.5 miles/hour) with a maximum horizontal deflection of 1/120 of opening width
- Design doors to withstand a temperature range of -20°F to +120°F (-29°C to +49°C)

1.3 Shop drawing: Supply shop drawings in accordance with plans and specifications for approval. Contractor shall be responsible for job site dimensions before fabrication and co-ordination with others sub-trades.

1.4 Maintenance instructions: Supply maintenance instructions for hardware and/or others components in accordance section 01300.

1.5 Warranty: The Glace-Guard Slider door and hardware carry a warranty of one (1) year against any defect or faulty workmanship.

PART 2 - PRODUCT

2.1 Materials :

- Pre-painted galvanised G-60 metal sheet conform to ASTM A653
- Commercial aluminum extrusions 6063 T5
- Insulation: foamed in place polyurethane, 2.56 lbs/ft³ (41.0 kg/m³) minimum density, conform to CGSB 51-GP-21M.

2.2 Reference product : Glace-Guard™ Slider III (3”), Glace-Guard™ Slider IV (4”), as manufactured by THERMOSTOP INC., 3775 Losch boulevard, Longueuil, (Québec), Canada, Tel.: 450-678-8666, Fax: 450-678-7765, www.thermostop.com

2.3 Dimensions and clearances :

<u>Quantity</u>	<u>Dimensions</u>	<u>Side clearances</u>
	(height x length)	

2.4 Temperature range:

Cooler: 4°C & above / 38 °F & above
 Freezer: -30°C to 2°C / -22 °F to 36 °F

2.5 Size:

Up to 14’0” W. X 16’0” H. (4267mm W. X 4877mm H.)



THERMOSTOP INC., 3775 Losch, Longueuil, Québec, Canada, J3Y 5T7, Tél. : (450) 678-8666, Fax. : (450) 678-7765

2.6 Thickness and insulation value:

3" (R-24) thick: Glace-Guard™ Slider III

4" (R-32) thick: Glace-Guard™ Slider IV

2.7 Panel manufacturing process: The inner core consists of rigid polyurethane, foamed in place under high pressure between two metal skins. To avoid mouldiness, no wood material is used in the construction of the panel.

2.8 Insulation: CFC-free rigid foamed-in-place polyurethane. 2.56 lbs/ft³ (41.0 kg/m³) minimum density .

2.9 Metal skins options:

26ga. steel skins, white stucco finish.

2.10 Single or biparting: Door can be single or biparting. Door panel framing is made of U-shaped heavy-duty aluminum extrusions.

2.11 Face frame and back frame:

Standard 1" thick extruded aluminum face frame, mill finish, to self support the door and hardware load. Optional back frame made with same material as face frame.

2.12 Heat trace (optional): For freezer applications, the door frame and panels are equipped with a heat trace to prevent ice or frost accumulation and to avoid the need of a heated threshold.

2.13 Kick plate (optional): 24" (610mm) high steel kick plate to protect the door bottom against forklift impacts, made of 1/16" thick aluminium checker plate or 1/8" thick aluminum checker plate.

2.14 Window (optional): Sealed glass or acrylic glass 12" x 24" (305mm x 610mm) windows. Optional heated sealed glass for freezer application.

2.15 Seals: High quality airtight compression seals on door frame and double bottom sweep seals.

2.16 Hardware: The hardware consists of a heavy-duty double track system and trolley assembly roller systems. The trolley assembly stabilizes the movements of the panels at high speed and is equipped with solid tire rollers to support an intensive usage. The track system is slanted from center to both ends to ensure a tight seal and to reduce seal wear. All components are made of aluminum or galvanized steel, or are zinc-coated for food applications.

2.17 Motor (optional):

AC one-speed motor:

- Worm gear motor
- 1.5 second time delay before direction reversing
- Safety pneumatic edge
- 12" per second on opening and closing
- 15" cycles maximum per hour
- Options for 115V, 230V, 460V or 600V
- Motor size: 10"W. x 13"H. x 11" depth

DC variable frequency motor:

- Brushless servomotor
- High speed operation: up to 48" (1220mm) per second at opening, for a bi-parting door



THERMOSTOP INC., 3775 Losch, Longueuil, Québec, Canada, J3Y 5T7, Tél. : (450) 678-8666, Fax. : (450) 678-7765

- Dimensions: 11" x 41/4" x 41/4"
- Closed loop control system to ensure accurate motion profile with changing loads
- Selectable input voltage, single or three phase: 115, 208, 230, 460 or 575V AC
- Programmable obstruction sensing
- Cycle counter
- LCD/Keypad display of system operation
- Electronic programmable clutch
- Electronic door lock protection
- Corrosion-resistant

PART 3 - INSTALLATION

- 3.1** Ensure the sliding door is level and square. Install door and others components as per manufacturer's instructions and building code.
- 3.2** Co-ordinate receiving goods on site. The installer provides proper equipment and labour to receive the materials on site.
- 3.3** Work will be done by approved and licensed installer.
- 3.4** Keep site clean and remove all unnecessary materials as the work progresses.
- 3.5** Correct deficiencies diligently as requested by site supervisor.